

Quick Reference Flange Chart

		PN6 5K 125 lbs			PN10 10K 150 lbs			PN16 16K 300 lbs			PN25 20K 300 lbs			PN40 40K 600 lbs		
		O.D.	B.C.	HOLES	O.D.	B.C.	HOLES	O.D.	B.C.	HOLES	O.D.	B.C.	HOLES	O.D.	B.C.	HOLES
10 3/8"	DIN	75	50	4 X 11	90	60	4 X 14	90	60	4 X 14	90	60	4 X 14	90	60	4 X 14
	JIS	75	55	4 X 12	90	65	4 X 15	90	65	4 X 15	90	65	4 X 15	110	75	4 X 19
	ANSI															
15 1/2"	DIN	80	55	4 X 11	95	65	4 X 14	95	65	4 X 14	95	65	4 X 14	95	65	4 X 14
	JIS	80	60	4 X 12	95	70	4 X 15	95	70	4 X 15	95	70	4 X 15	115	80	4 X 19
	ANSI				89	60	4 X 16	95	67	4 X 16	95	67	4 X 16	95	67	4 X 16
20 3/4"	DIN	90	65	4 X 11	105	75	4 X 14	105	75	4 X 14	105	75	4 X 14	105	75	4 X 14
	JIS	85	65	4 X 12	100	75	4 X 15	100	75	4 X 15	100	75	4 X 15	120	85	4 X 19
	ANSI				99	70	4 X 16	117	83	4 X 20	117	83	4 X 20	117	82	4 X 19
25 1"	DIN	100	75	4 X 11	115	85	4 X 14	115	85	4 X 14	115	85	4 X 14	115	85	4 X 14
	JIS	95	75	4 X 12	125	90	4 X 19	125	90	4 X 19	125	90	4 X 19	130	95	4 X 19
	ANSI	108	80	4 X 16	108	80	4 X 16	124	89	4 X 20	124	89	4 X 20	124	89	4 X 19
32 1-1/4"	DIN	120	90	4 X 14	140	100	4 X 18	140	100	4 X 18	140	100	4 X 18	140	100	4 X 18
	JIS	115	90	4 X 15	135	100	4 X 19	135	100	4 X 19	135	100	4 X 19	140	105	4 X 19
	ANSI	118	89	4 X 16	118	89	4 X 16	133	98	4 X 20	133	98	4 X 20	133	98	4 X 19
40 1-1/2"	DIN	130	100	4 X 14	150	110	4 X 18	150	110	4 X 18	150	110	4 X 18	150	110	4 X 18
	JIS	120	95	4 X 15	140	105	4 X 19	140	105	4 X 19	140	105	4 X 19	160	120	4 X 23
	ANSI	127	98	4 X 16	127	98	4 X 16	156	114	4 X 23	156	114	4 X 23	156	114	4 X 22
50 2"	DIN	140	110	4 X 14	165	125	4 X 18	165	125	4 X 18	165	125	4 X 18	165	125	4 X 18
	JIS	130	105	4 X 15	155	120	4 X 19	155	120	8 X 19	155	120	8 X 19	165	130	8 X 19
	ANSI	152	121	4 X 20	152	121	4 X 20	165	127	8 X 20	165	127	8 X 20	165	127	8 X 19
65 2-1/2"	DIN	160	130	4 X 14	185	145	4 X 18	185	145	4 X 18	185	145	8 X 18	185	145	8 X 18
	JIS	155	130	4 X 15	175	140	4 X 19	175	140	8 X 19	175	140	8 X 19	200	160	8 X 23
	ANSI	178	140	4 X 20	178	140	4 X 20	190	149	8 X 23	190	149	8 X 23	190	149	8 X 23
80 3"	DIN	190	150	4 X 18	200	160	4 X 18	200	160	8 X 18	200	160	8 X 18	200	160	8 X 18
	JIS	180	145	4 X 19	185	150	8 X 19	200	160	8 X 23	200	160	8 X 23	210	170	8 X 23
	ANSI	190	152	4 X 20	190	152	4 X 20	210	168	8 X 23	210	168	8 X 23	210	168	8 X 23
100 4"	DIN	210	170	4 X 18	220	180	8 X 18	220	180	8 X 18	235	190	8 X 22	235	190	8 X 22
	JIS	200	165	8 X 19	210	175	8 X 19	225	185	8 X 23	225	185	8 X 23	250	205	8 X 25
	ANSI	229	190	8 X 20	229	190	8 X 20	254	200	8 X 23	254	200	8 X 23	273	216	8 X 26

Quick Reference Flange Chart

		PN6 5K 125 lbs			PN10 10K 150 lbs			PN16 16K 300 lbs			PN25 20K 300 lbs			PN40 40K 600 lbs		
		O.D.	B.C.	HOLES	O.D.	B.C.	HOLES	O.D.	B.C.	HOLES	O.D.	B.C.	HOLES	O.D.	B.C.	HOLES
125	DIN	240	200	8 X 18	250	210	8 X 18	250	210	8 X 18	270	220	8 X 26	270	220	8 X 26
	JIS	235	200	8 X 19	250	210	8 X 23	270	225	8 X 25	270	225	8 X 25	300	250	8 X 27
	ANSI	254	216	8 X 23	254	216	8 X 23	279	235	8 X 23	279	235	8 X 23	330	266	8 X 29
150	DIN	265	225	8 X 18	285	240	8 X 22	285	240	8 X 22	300	250	8 X 26	300	250	8 X 26
	JIS	265	230	8 X 19	280	240	8 X 23	305	260	12 X 25	305	260	12 X 25	355	295	12 X 33
	ANSI	279	241	8 X 23	279	241	8 X 23	318	270	12 X 23	318	270	12 X 23	355	292	12 X 29
175	DIN				315	270	8 X 22	315	270	8 X 22	330	280	12 X 26	350	295	12 X 30
	JIS	300	260	8 X 23	305	265	12 X 23									
	ANSI															
200	DIN	320	280	8 X 18	340	295	8 X 22	340	295	12 X 22	360	310	12 X 26	375	320	12 X 30
	JIS	320	280	8 X 23	330	290	12 X 23	350	305	12 X 25	350	305	12 X 25	405	345	12 X 33
	ANSI	343	298	8 X 23	343	298	8 X 23	381	330	12 X 23	381	330	12 X 23	419	349	12 X 32
250	DIN	375	335	12 X 18	395	350	12 X 22	405	355	12 X 26	425	370	12 X 30	450	385	12 X 33
	JIS	385	345	12 X 23	400	355	12 X 25	430	380	12 X 27	430	380	12 X 27	475	410	12 X 33
	ANSI	406	362	12 X 26	406	362	12 X 26	445	387	16 X 32	445	387	16 X 32	508	432	16 X 35
300	DIN	440	395	12 X 22	445	400	12 X 22	460	410	12 X 26	485	430	16 X 30	515	450	16 X 33
	JIS	430	390	12 X 23	445	400	16 X 25	480	430	16 X 27	480	430	16 X 27	540	470	16 X 39
	ANSI	482	431	12 X 26	482	431	12 X 26	520	450	16 X 35	520	450	16 X 35	558	489	20 X 35
350	DIN	490	445	12 X 22	505	460	16 X 22	520	470	16 X 26	555	490	16 X 33	580	510	16 X 36
	JIS	480	435	12 X 25	490	445	16 X 25	540	480	16 X 33	540	480	16 X 33	585	515	16 X 39
	ANSI	533	476	12 X 29	533	476	12 X 28	584	514	20 X 35	584	514	20 X 35	603	527	20 X 38
400	DIN	540	495	16 X 22	565	515	16 X 26	580	525	16 X 30	620	550	16 X 36	660	585	16 X 39
	JIS	540	495	16 X 25	560	510	16 X 27	605	540	16 X 33	605	540	16 X 33	645	570	16 X 39
	ANSI	597	540	16 X 29	597	540	16 X 29	648	571	20 X 38	648	571	20 X 38	685	603	20 X 42
450	DIN	595	550	16 X 22	615	565	20 X 26	640	585	20 X 30	670	600	20 X 36	685	610	20 X 39
	JIS	605	555	16 X 25	620	565	20 X 27	675	605	20 X 33	675	605	20 X 33			
	ANSI				635	578	16 X 32	710	629	24 X 35	710	629	24 X 35	745	654	20 X 45
500	DIN	645	600	20 X 22	670	620	20 X 26	715	650	20 X 33	730	660	20 X 36	755	670	20 X 42
	JIS	655	605	20 X 25	675	620	20 X 27	730	660	20 X 33	730	660	20 X 33			
	ANSI	698	635	20 X 32	698	635	20 X 32	775	685	24 X 38	775	685	24 X 38	812	733	24 X 45

[illegible]